

# AESCO/MADSEN

## Hammermill RAP Crusher

AESCO/MADSEN's Hammermill RAP Crusher is a single-shaft hammermill style crusher designed to pulverize RAP material up to 8" in size. Capacities are determined by the product discharge size, feed components and feed size.

### Specifications:

Feed opening: 48" x 15"

Discharge Opening: 30.5" x 39.5"

Width: 50" overall

Length: 73" overall

Height: 60" overall

Weight: 6000 lbs. (less motor and sheaves)

**Hammers:** This versatile piece of equipment allows the hammers to be mounted in either two or four rows. The hammers are cast high chrome white iron for superior impact-resistance and impregnated with Tungsten Carbide for a long life.



**Rotor:** The rotor shaft is 2-15/16" chrome Moly precision steel. Eight rotor disks are welded to a common hub, which is secured to the 2-15/16" drive shaft. The rotor can accommodate two or four 1-1/4" hammer rods. The hammer rods are held in place by heavy-duty plates, bolted in place on the outside of the rotor and disks.

**Housing:** The housing is manufactured of 3/4" thick, A36 steel plate. The housing consists of a fabricated steel base, a bolted in place top section and hinged section, which provides access to the rotor. The interior of the housing is lined with bolt in place 7/8" thick high chrome white iron wear plates.

**Grate Screens:** Five grates slide in place under the hammermill. They are impregnated with Tungsten Carbide for an extended service life. Available in several standard opening specifications.

Call or Fax Your AESCO/MADSEN Sales Rep Today  
253-939-4150 • Fax 253-939-1576



1531 20th Street Northwest • Auburn, Washington 98001-3422  
www.aescomadsen.com • email: sales@aescomadsen.com